



SUBFLOOR FASTENING / COIL AND STRIP

STAND-UP OPERATION. 150 SCREWS PER FILL. THE SUBFLOOR SYSTEM THAT DOESN'T STOP.

CS series twinfast coil runs 150 screws per fill on the FDVL43. That's 5x fewer reloads than strip format across a full floor. Stand-up T-handle. Adjustable depth control. Yellow zinc for standard subfloor and underlayment. Strip option on CH7392SF for crews who need it.

- 150-screw coil on FDVL43: 5x fewer reloads than strip format
- Twinfast thread pulls tight without blowout on engineered panels
- Yellow zinc for standard interior subfloor and underlayment
- Adjustable depth control: repeatable countersink on every panel
- Stand-up T-handle: no bending across the floor all day
- Strip option on CH7392SF: 30 per fill for smaller crews
- Sizes #8 x 1-1/4" through #10 x 3"

COIL / FDVL43

CS8114Y #8 x 1-1/4" Yellow Zinc 3,600/box \$43.00

CS8112Y #8 x 1-1/2" Yellow Zinc 2,700/box \$43.00

CS8212YLP #8 x 2-1/2" Yellow Zinc 1,800/box \$48.00

STRIP / CH7392SF

CS8112YMSU #8 x 1-1/2" Yellow Zinc 2,100/box \$40.00

CS8212YMSU #8 x 2-1/2" Yellow Zinc 1,500/box \$40.00

THE SYSTEM

FDVL43 Speed Driver

150-screw coil. Stand-up T-handle. Depth control.

CS8114Y

\$43.00

#8 x 1-1/4" YZ Coil 3,600/box

CS8212YLP

\$48.00

#8 x 2-1/2" YZ Coil 1,800/box

CH7392SF Strip Driver

30 per fill. Subfloor and underlayment.

CS8212YMSU

\$40.00

#8 x 2-1/2" YZ Strip 1,500/box

COIL VS STRIP: WHY IT MATTERS

150 screws per fill on the FDVL43 vs 30 per fill on the CH7392SF strip. On a 2,000 sq ft floor, coil format means 5x fewer stops. That's time on the floor, not at the reload station.

ALSO USED IN

Underlayment / Wood Sheathing
Light Commercial / Multifamily

CS SERIES

YELLOW ZINC TWINFAST SUBFLOOR AND UNDERLAYMENT FDVL43 + CH7392SF

Twinfast coarse thread coil and strip for subfloor and underlayment. Yellow zinc for standard interior exposure. Coil on FDVL43 (150 per fill). Strip on CH7392SF (30 per fill). Sizes #8 x 1-1/4" through #10 x 3".

- Twinfast coarse thread: pulls tight without blowout on engineered panels
- Yellow zinc: standard interior subfloor exposure
- Coil: FDVL43 (150/fill). Strip: CH7392SF (30/fill).
- #2 Square drive on both formats

COIL / FDVL43

CS8114Y #8 x 1-1/4" 3,600/box \$43.00
CS8112Y #8 x 1-1/2" 2,700/box \$43.00
CS8134Y #8 x 1-3/4" 2,700/box \$43.00
CS8134YLP #8 x 1-3/4" LP 2,700/box \$43.00
CS8200YLP #8 x 2" LP 1,800/box \$43.00
CS8212YLP #8 x 2-1/2" LP 1,800/box \$48.00
CS0212BLP #10 x 2-1/2" Bright Zinc 1,800/box \$67.00

STRIP / CH7392SF

CS8112YMSU #8 x 1-1/2" 2,100/box \$40.00
CS8134YMSU #8 x 1-3/4" 1,800/box \$40.00
CS8200YMSU #8 x 2" 1,800/box \$40.00
CS8212YMSU #8 x 2-1/2" 1,500/box \$40.00
CS8300YMSU #8 x 3" 1,200/box \$40.00
CS0300YMSU #10 x 3" 1,200/box \$85.00

KEY SPECS AT A GLANCE

Thread	Twinfast coarse
Finish	Yellow zinc
Drive	#2 Square
Coil tool	FDVL43 (150/fill)
Strip tool	CH7392SF (30/fill)
Sizes	1-1/4" to 3"

STAINLESS OPTION

For treated lumber or moisture-exposed applications: CS8200SLP-T17 (\$214.00) and CS8212SLP-T17 (\$223.00). 305 SS Type 17 tip. Ask for quote on 316 SS option for coastal subfloor and deck.

COMPATIBLE TOOLS

FDVL43 (coil, 150/fill)
CH7392SF (strip, 30/fill, subfloor dedicated)